

LIFTING DEVICE FOR:




 FALL
 PROTECTION
 ANCHORAGE POINTS

The new RUD-Fall Protection Anchorage Points **PSA-VRS (STARPOINT)** and **PSA-INOX-STAR** have been developed especially for the use of personal protection equipment (PPE).

To guarantee the high safety requirements for the use of personal protection equipment, the RUD-Fall Protection Anchorage Points are certified by the German BG (Employers Liability Insurance Association).

The components are in accordance with the European Directive 89/686/EWG and marked with EN 795 and the CE mark as well as the safe working load limit (in persons - 1 Pers / 2 Pers).





We are pleased to advise without obligation!

CONVINCING RUD-PLUS FACTOR FOR PSA-FALL PROTECTION ANCHORAGE POINTS

- Certified and tested by the German BG (Employers Liability Insurance Association)
- EG-Prototype test approval PS 08060001
- stainless PSA INOX STAR suitable for permanent outdoor-use
- fool-proofed assembled inner hexagon bolt
- clear distinction in shape and marking compared with the normal eye bolt DIN 580
- available in different thread lengths (see below)
- optical eye-catcher due to the coating
- for large quantities, an individual color can be requested.
- 100 % crack detected
- also in M16 and M20 (for 2 Pers.)



PSA-VRS and PSA-INOX-STAR M12 and M16

- Basic test requirements:
DIN EN 795;1996/A1:2001
DIN EN 50308:2005/03 chapter 4.5 and OSHA 1926.502:2001/01 chapter (d)(15) and AS/NZS 1891.4:2009 (M16 only)
- dynamic fall test carried out with 150 kg (required are 100 kg)
- Marking of components acc. to DIN EN 365
- Proof force : 22,2 kN/ Person or 5000 lbs / Person

Typ	WLL	Thread	D	E	T	L Std	L Max	Weight	Ref. No.	
PSA-INOX-STAR-EYEBOLT M12	1 Pers.	M12	30mm	30mm	56mm	18mm	18-150 mm	0.2 kg	7997097	7997820
PSA-INOX-STAR-EYEBOLT M 16	2 Pers.	M16	35mm	35mm	65mm	24mm	24-120 mm	0.3 kg	7996757	-
PSA-INOX-STAR-EYEBOLT M20	2 Pers.	M20	40mm	43mm	74mm	30mm	-	0.53 kg	7900921	-
PSA-VRS STARPOINT M12	1 Pers.	M12	30mm	30mm	56mm	18mm	18-150 mm	0.2 kg	7997100	8600400
PSA-VRS STARPOINT M16	2 Pers.	M16	35mm	35mm	65mm	24mm	24-120 mm	0.3 kg	7997854	8600401
PSA-VRS STARPOINT M20	2 Pers.	M20	40mm	42mm	75mm	30mm	-	0.56 kg	7900920	-
PSA-STARPOINT VRS-1/2"-13UNC	1 Pers.	1/2"- 13 UNC	1-3/16"	1-3/16"	2-3/16"	3/4"	-	0.44 lbs	7997103	-
PSA-STARPOINT VRS-5/8"-11UNC	2 Pers.	5/8"- 11UNC	1-3/8"	1-3/8"	2-9/16"	15/16"	-	0.66 lbs	7998659	-

* Vario lengths require a minimum order quantity and may have and extended delivery time. Please indicate length upon request.